



MiniSKiiP® PACK 2

1200 V / 50 A

Topology features

- Inverter
- Kelvin Emitter for improved switching performance
- Open Emitter configuration
- Temperature sensor

Component features

- Easy paralleling
- Low turn-off losses
- Low collector emitter saturation voltage
- Positive temperature coefficient
- Short tail current
- Switching optimized for EMC

Housing features

- Base isolation: Al<sub>2</sub>O<sub>3</sub>
- Easy assembly in one mounting step
- Flexible PCB design w/o pin holes
- Rugged solderless spring contacts

Extra features

- SKiiP 25AC12T4V25


Target applications

- Elevator Drives


Types

- 80-M2126PB050M701-K359F70

MiniSKiiP® 2 16 mm housing



Schematic





Vincotech

## Maximum Ratings

$T_j = 25\text{ °C}$ , unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
<b>Inverter Switch</b>				
Collector-emitter voltage	$V_{CES}$		1200	V
Collector current (DC current)	$I_C$	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	68	A
Repetitive peak collector current	$I_{CRM}$	$t_p$ limited by $T_{jmax}$	100	A
Total power dissipation	$P_{tot}$	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	151	W
Gate-emitter voltage	$V_{GES}$		$\pm 20$	V
Short circuit ratings	$t_{SC}$	$V_{GE} = 15\text{ V}$ , $V_{CC} = 800\text{ V}$ $T_j = 150\text{ °C}$	9,5	$\mu\text{s}$
Maximum junction temperature	$T_{jmax}$		175	$^{\circ}\text{C}$

## Inverter Diode

Peak repetitive reverse voltage	$V_{RRM}$		1200	V
Forward current (DC current)	$I_F$	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	55	A
Repetitive peak forward current	$I_{FRM}$	$t_p$ limited by $T_{jmax}$	100	A
Total power dissipation	$P_{tot}$	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	105	W
Maximum junction temperature	$T_{jmax}$		175	$^{\circ}\text{C}$

## Module Properties

### Thermal Properties

Storage temperature	$T_{stg}$		-40...+125	$^{\circ}\text{C}$
Operation temperature under switching condition	$T_{jop}$		-40...+( $T_{jmax} - 25$ )	$^{\circ}\text{C}$

### Isolation Properties

Isolation voltage	$V_{isol}$	DC Test Voltage* $t_p = 2\text{ s}$	5500	V
Isolation voltage	$V'_{isol}$	AC Voltage $t_p = 1\text{ min}$	2500	V
Creepage distance		With std lid For more informations see handling instructions	6,3	mm
Clearance		With std lid For more informations see handling instructions	6,3	mm
Comparative Tracking Index	CTI		$\geq 600$	

\*100 % tested in production



Vincotech

80-M2126PB050M701-K359F70  
datasheet

### Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		$V_{GE}$ [V] $V_{GS}$ [V]	$V_{CE}$ [V] $V_{DS}$ [V] $V_F$ [V]	$I_C$ [A] $I_D$ [A] $I_F$ [A]	$T_j$ [°C]	Min	Typ	Max		

#### Inverter Switch

##### Static

Gate-emitter threshold voltage	$V_{GE(th)}$		10	0,005	25	5,4	6	6,6	V
Collector-emitter saturation voltage	$V_{CE(sat)}$	15		50	25 125 150		1,55 1,77 1,83	1,9 <sup>(1)</sup>	V
Collector-emitter cut-off current	$I_{CES}$	0	1200		25			0,09	mA
Gate-emitter leakage current	$I_{GES}$	20	0		25			0,5	μA
Internal gate resistance	$r_g$						None		Ω
Input capacitance	$C_{ies}$						10000		pF
Output capacitance	$C_{oes}$	0	10		25		350		pF
Reverse transfer capacitance	$C_{res}$						130		pF
Gate charge	$Q_g$	$V_{CC} = 600$ V	0/15		50	25	380		nC

##### Thermal

Thermal resistance junction to sink <sup>(2)</sup>	$R_{th(j-s)}$	$\lambda_{paste} = 2,5$ W/mK (HPTP)					0,63		K/W
--	---------------	--	--	--	--	--	------	--	-----

##### Dynamic

Turn-on delay time	$t_{d(on)}$					25 125 150		62,74 61,98 61,76	ns
Rise time	$t_r$	$R_{gon} = 4$ Ω $R_{goff} = 4$ Ω				25 125 150		15,01 17,64 18,12	ns
Turn-off delay time	$t_{d(off)}$		-5/15	600	50	25 125 150		174,36 201,46 207,79	ns
Fall time	$t_f$					25 125 150		106,63 107,63 115,47	ns
Turn-on energy (per pulse)	$E_{on}$	$Q_{tFWD} = 4,63$ μC $Q_{tFWD} = 7,49$ μC $Q_{tFWD} = 8,23$ μC				25 125 150		2,91 3,84 4,12	mWs
Turn-off energy (per pulse)	$E_{off}$					25 125 150		3,59 4,84 5,16	mWs



Vincotech

**80-M2126PB050M701-K359F70**  
datasheet

### Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		$V_{GE}$ [V] $V_{GS}$ [V]	$V_{CE}$ [V] $V_{DS}$ [V] $V_F$ [V]	$I_C$ [A] $I_D$ [A] $I_F$ [A]	$T_j$ [°C]	Min	Typ	Max		
<b>Inverter Diode</b>										
<b>Static</b>										
Forward voltage	$V_F$			50	25 125 150		1,66 1,78 1,79	2,1 <sup>(1)</sup>		V
Reverse leakage current	$I_R$	$V_r = 1200$ V			25			40		μA
<b>Thermal</b>										
Thermal resistance junction to sink <sup>(2)</sup>	$R_{th(j-s)}$	$\lambda_{paste} = 2,5$ W/mK (HPTP)					0,91			K/W
<b>Dynamic</b>										
Peak recovery current	$I_{RM}$				25 125 150		49,26 52,32 53,42			A
Reverse recovery time	$t_{rr}$				25 125 150		254,16 404,77 434,11			ns
Recovered charge	$Q_r$	$di/dt=1910$ A/μs $di/dt=1799$ A/μs $di/dt=1725$ A/μs	-5/15	600	50	25 125 150	4,63 7,49 8,23			μC
Reverse recovered energy	$E_{rec}$				25 125 150		1,87 3,19 3,55			mWs
Peak rate of fall of recovery current	$(di_r/dt)_{max}$				25 125 150		1123,16 566,82 517,36			A/μs



Vincotech

### Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		$V_{GS}$ [V]	$V_{GE}$ [V]	$V_{DS}$ [V]	$V_{CE}$ [V]	$T_j$ [°C]	Min	Typ	Max	

### Thermistor

#### Static

Rated resistance	$R$					25		1		kΩ
Deviation of R100	$A_{R/R}$	$R_{100} = 1670 \Omega$				100	-2		2	%
Maximum Current	$I_{max}$							3		mA
Power dissipation constant	$d$					25		0,76		mW/K
A-value	$A$							$7,635 \times 10^{-3}$		1/K
B-value	$B$							$1,73 \times 10^{-5}$		1/K <sup>2</sup>
Vincotech Thermistor Reference									E	

<sup>(1)</sup> Value at chip level


<sup>(2)</sup> Only valid with pre-applied Vincotech thermal interface material.



## Inverter Switch Characteristics

**figure 1.** IGBT

Typical output characteristics  
 $I_C = f(V_{CE})$




$t_p = 250 \mu s$   
 $V_{GE} = 15 V$

$T_j:$  — 25 °C  
— 125 °C  
— 150 °C

**figure 2.** IGBT


Typical output characteristics  
 $I_C = f(V_{CE})$



$t_p = 250 \mu s$   
 $T_j = 150 \text{ °C}$   
 $V_{GE}$  from 7 V to 17 V in steps of 1 V

**figure 3.** IGBT

Typical transfer characteristics  
 $I_C = f(V_{GE})$




$t_p = 250 \mu s$   
 $V_{CE} = 10 V$

$T_j:$  — 25 °C  
— 125 °C  
— 150 °C

**figure 4.** IGBT

Transient thermal impedance as a function of pulse width  
 $Z_{th(j-s)} = f(t_p)$



$D = t_p / T$   
 $R_{th(j-s)} = 0,63 \text{ K/W}$

IGBT thermal model values


$R$ (K/W)	$\tau$ (s)
5,38E-02	2,36E+00
1,33E-01	3,13E-01
3,14E-01	6,13E-02
8,40E-02	1,01E-02
4,51E-02	6,01E-04



## Inverter Switch Characteristics

**figure 5.** IGBT


Safe operating area  
 $I_C = f(V_{CE})$



$D =$  single pulse  
 $T_s = 80 \text{ } ^\circ\text{C}$   
 $V_{GE} = 15 \text{ V}$   
 $T_j = T_{jmax}$

**figure 6.** IGBT

Gate voltage vs gate charge  
 $V_{GE} = f(Q_g)$



$I_C = 50 \text{ A}$   
 $T_j = 25 \text{ } ^\circ\text{C}$




## Inverter Diode Characteristics

**figure 7.** FWD

Typical forward characteristics


$$I_F = f(V_F)$$



**figure 8.** FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = \frac{t_p}{T}$   
 $R_{th(j-s)} = 0,905 \text{ K/W}$   
 FWD thermal model values

R (K/W)	$\tau$ (s)
5,27E-02	2,69E+00
1,50E-01	2,53E-01
4,30E-01	5,39E-02
1,76E-01	9,78E-03
9,64E-02	8,96E-04






## Thermistor Characteristics

figure 9. Thermistor

Typical PTC characteristic as function of temperature

$$R_T = f(T)$$






## Inverter Switching Characteristics

**figure 10.** IGBT

Typical switching energy losses as a function of collector current  
 $E = f(I_c)$




With an inductive load at  
 $V_{CE} = 600 \text{ V}$   
 $V_{GE} = -5/15 \text{ V}$   
 $R_{g\text{on}} = 4 \ \Omega$   
 $R_{g\text{off}} = 4 \ \Omega$

$T_j$ : — 25 °C  
— 125 °C  
— 150 °C

**figure 11.** IGBT

Typical switching energy losses as a function of IGBT turn on gate resistor  
 $E = f(R_g)$




With an inductive load at  
 $V_{CE} = 600 \text{ V}$   
 $V_{GE} = -5/15 \text{ V}$   
 $I_c = 50 \text{ A}$

$T_j$ : — 25 °C  
— 125 °C  
— 150 °C

**figure 12.** FWD

Typical reverse recovered energy loss as a function of collector current  
 $E_{rec} = f(I_c)$




With an inductive load at  
 $V_{CE} = 600 \text{ V}$   
 $V_{GE} = -5/15 \text{ V}$   
 $R_{g\text{on}} = 4 \ \Omega$

$T_j$ : — 25 °C  
— 125 °C  
— 150 °C

**figure 13.** FWD

Typical reverse recovered energy loss as a function of IGBT turn on gate resistor  
 $E_{rec} = f(R_g)$



With an inductive load at  
 $V_{CE} = 600 \text{ V}$   
 $V_{GE} = -5/15 \text{ V}$   
 $I_c = 50 \text{ A}$


$T_j$ : — 25 °C  
— 125 °C  
— 150 °C



## Inverter Switching Characteristics

**figure 14.** IGBT


Typical switching times as a function of collector current  
 $t = f(I_c)$



With an inductive load at  
 $T_j = 150 \text{ }^\circ\text{C}$   
 $V_{CE} = 600 \text{ V}$   
 $V_{GE} = -5/15 \text{ V}$   
 $R_{gon} = 4 \text{ } \Omega$   
 $R_{goff} = 4 \text{ } \Omega$

**figure 15.** IGBT


Typical switching times as a function of IGBT turn on gate resistor  
 $t = f(R_g)$



With an inductive load at  
 $T_j = 150 \text{ }^\circ\text{C}$   
 $V_{CE} = 600 \text{ V}$   
 $V_{GE} = -5/15 \text{ V}$   
 $I_c = 50 \text{ A}$

**figure 16.** FWD


Typical reverse recovery time as a function of collector current  
 $t_{rr} = f(I_c)$



With an inductive load at  
 $V_{CE} = 600 \text{ V}$   
 $V_{GE} = -5/15 \text{ V}$   
 $R_{gon} = 4 \text{ } \Omega$   
 $T_j:$  — 25 °C  
 — 125 °C  
 — 150 °C

**figure 17.** FWD

Typical reverse recovery time as a function of IGBT turn on gate resistor  
 $t_{rr} = f(R_{gon})$



With an inductive load at  
 $V_{CE} = 600 \text{ V}$   
 $V_{GE} = -5/15 \text{ V}$   
 $I_c = 50 \text{ A}$   
 $T_j:$  — 25 °C  
 — 125 °C  
 — 150 °C




## Inverter Switching Characteristics

**figure 18.** FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$



With an inductive load at


$V_{CE} = 600 \text{ V}$   
 $V_{GE} = -5/15 \text{ V}$   
 $R_{gon} = 4 \ \Omega$

$T_j$ : — 25 °C  
— 125 °C  
— 150 °C

**figure 19.** FWD

Typical recovered charge as a function of IGBT turn on gate resistor

$$Q_r = f(R_{gon})$$



With an inductive load at


$V_{CE} = 600 \text{ V}$   
 $V_{GE} = -5/15 \text{ V}$   
 $I_c = 50 \text{ A}$

$T_j$ : — 25 °C  
— 125 °C  
— 150 °C

**figure 20.** FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_c)$$



With an inductive load at


$V_{CE} = 600 \text{ V}$   
 $V_{GE} = -5/15 \text{ V}$   
 $R_{gon} = 4 \ \Omega$

$T_j$ : — 25 °C  
— 125 °C  
— 150 °C

**figure 21.** FWD

Typical peak reverse recovery current as a function of IGBT turn on gate resistor

$$I_{RM} = f(R_{gon})$$



With an inductive load at

$V_{CE} = 600 \text{ V}$   
 $V_{GE} = -5/15 \text{ V}$   
 $I_c = 50 \text{ A}$


$T_j$ : — 25 °C  
— 125 °C  
— 150 °C



## Inverter Switching Characteristics

**figure 22.** FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current  
 $di_f/dt, di_{rr}/dt = f(I_c)$




With an inductive load at  
 $V_{CE} = 600 \text{ V}$   
 $V_{GE} = -5/15 \text{ V}$   
 $R_{gon} = 4 \text{ } \Omega$

$T_j$ :  
— 25 °C  
— 125 °C  
— 150 °C

**figure 23.** FWD

Typical rate of fall of forward and reverse recovery current as a function of turn on gate resistor  
 $di_f/dt, di_{rr}/dt = f(R_{gon})$




With an inductive load at  
 $V_{CE} = 600 \text{ V}$   
 $V_{GE} = -5/15 \text{ V}$   
 $I_c = 50 \text{ A}$

$T_j$ :  
— 25 °C  
— 125 °C  
— 150 °C

**figure 24.** IGBT

Reverse bias safe operating area  
 $I_c = f(V_{CE})$




At  $T_j = 150 \text{ } ^\circ\text{C}$   
 $R_{gon} = 4 \text{ } \Omega$   
 $R_{goff} = 4 \text{ } \Omega$



## Inverter Switching Definitions


**figure 25.** IGBT

Turn-off Switching Waveforms & definition of  $t_{doff}$ ,  $t_{Eoff}$  ( $t_{Eoff}$  = integrating time for  $E_{off}$ )




**figure 26.** IGBT

Turn-on Switching Waveforms & definition of  $t_{don}$ ,  $t_{Eon}$  ( $t_{Eon}$  = integrating time for  $E_{on}$ )




**figure 27.** IGBT

Turn-off Switching Waveforms & definition of  $t_f$



**figure 28.** IGBT

Turn-on Switching Waveforms & definition of  $t_r$





### Inverter Switching Definitions


figure 29. FWD

Turn-off Switching Waveforms & definition of  $t_{rr}$



figure 30. FWD


Turn-on Switching Waveforms & definition of  $t_{Qr}$  ( $t_{Qr}$  = integrating time for  $Q_r$ )






Vincotech

Ordering Code	
Version	Ordering Code
With std lid (6.5mm height) + no thermal grease	80-M2126PB050M701-K359F70-/0A/
With thin lid (2.8mm height) + no thermal grease	80-M2126PB050M701-K359F70-/0B/
With std lid (6.5mm height) + thermal grease (0,8 W/mK, P12, silicone-based)	80-M2126PB050M701-K359F70-/1A/
With thin lid (2.8mm height) + thermal grease (0,8 W/mK, P12, silicone-based)	80-M2126PB050M701-K359F70-/1B/
With std lid (6.5mm height) + thermal grease (2,5 W/mK, TG20032, silicone-free)	80-M2126PB050M701-K359F70-/4A/
With thin lid (2.8mm height) + thermal grease (2,5 W/mK, TG20032, silicone-free)	80-M2126PB050M701-K359F70-/4B/
With std lid (6.5mm height) + thermal grease (2,5 W/mK, HPTP, silicone-based)	80-M2126PB050M701-K359F70-/5A/
With thin lid (2.8mm height) + thermal grease (2,5 W/mK, HPTP, silicone-based)	80-M2126PB050M701-K359F70-/5B/

Marking						
Text	Name		Date code	UL & VIN	Lot	Serial
		NN-NNNNNNNNNNNNNN- TTTTTTVV		WWYY	UL VIN	LLLLL
Datamatrix		Type&Ver	Lot number	Serial	Date code	
	TTTTTTVV	LLLLL	SSSS	WWYY		

Outline							
Pin table [mm]							
Pin	X	Y	Function	34	not assembled		
1	24,38	-21,8	DC+123	35	not assembled		
2	24,38	-18,6	DC+123	36	0,03	12,2	Ph1
3	24,38	-15,4	DC+123	37	0,03	15,4	Ph1
4	24,38	-12,2	DC+123	38	0,03	18,6	Ph1
5	not assembled			39	0,03	21,8	Ph1
6	not assembled			40	-8,5	-21,8	S15
7	not assembled			41	-8,5	-18,6	G15
8	24,38	12,2	Therm1	42	not assembled		
9	not assembled			43	not assembled		
10	not assembled			44	not assembled		
11	24,38	21,8	Therm2	45	-12,22	-5,8	Ph2
12	not assembled			46	not assembled		
13	not assembled			47	-12,22	3,9	Ph2
14	not assembled			48	-12,22	7,1	Ph2
15	not assembled			49	not assembled		
16	13,42	-21,8	G16	50	not assembled		
17	not assembled			51	-12,22	18,6	G11
18	not assembled			52	-12,22	21,8	S11
19	not assembled			53	-24,38	-21,8	DC-3
20	not assembled			54	-24,38	-18,6	DC-3
21	not assembled			55	-24,38	-15,4	DC-3
22	8,38	2,6	S14	56	not assembled		
23	8,38	5,8	G14	57	not assembled		
24	not assembled			58	-24,38	-5,8	DC-2
25	not assembled			59	-24,38	-2,5	DC-2
26	8,38	18,6	S12	60	-24,38	0,7	DC-2
27	8,38	21,8	G12	61	-24,38	3,9	S13
28	2,38	-21,8	S16	62	-24,38	7,1	G13
29	2,46	-18,6	Ph3	63	-24,38	15,4	DC-1
30	2,46	-15,4	Ph3	64	-24,38	18,6	DC-1
31	2,46	-12,2	Ph3	65	-24,38	21,8	DC-1
32	2,46	-9	Ph3				
33	not assembled						




Pad positions refers to center point. For more informations on pad design please see package data





Vincotech



Identification					
ID	Component	Voltage	Current	Function	Comment
T11, T12, T13, T14, T15, T16	IGBT	1200 V	50 A	Inverter Switch	
D11, D12, D13, D14, D15, D16	FWD	1200 V	50 A	Inverter Diode	
Rt	Thermistor			Thermistor	




Vincotech

Packaging instruction				
Standard packaging quantity (SPQ) 72	>SPQ	Standard	<SPQ	Sample

Handling instruction
Handling instructions for MiniSKiiP® 2 packages see vincotech.com website.

Package data
Package data for MiniSKiiP® 2 packages see vincotech.com website.

Vincotech thermistor reference
See Vincotech thermistor reference table at vincotech.com website.

UL recognition and file number
This device is certified according to UL 1557 standard, UL file number E192116. For more information see vincotech.com website. 

Document No.:	Date:	Modification:	Pages
80-M2126PB050M701-K359F70-D1-14	13 Jul. 2023		

**DISCLAIMER**

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

**LIFE SUPPORT POLICY**

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.